

No. SH10009758/TX

Date: Jan 27, 2010

Page 1 of 5

ELIM MEDICAL TECHNOLOGY (SUZHOU) CO., LTD 409-410, MULTI-FUNCTIONAL BUILDING, HIGH-TECH VENTURE PARK, WUJIANG, JIANGSU

The following sample(s) was/were submitted and identified on behalf of the client as:

Sample Description

: One sample of non-woven cutting in blue for disposable hospital curtain

Manufacturer

: ELIM MEDICAL TECHNOLOGY (SUZHOU) CO., LTD.

Test Performed

: Selected test(s) as requested by applicant

Sample Receiving Date

: JAN. 16, 2010

Testing Period

: JAN. 18, 2010 - JAN. 27, 2010

Test Result(s)

: For further details, please refer to the following page(s).

Signed for and on behalf of SGS-CSTC Ltd

Abe Bian (Account Executive)

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability entance is a function of the following of the following

0081438 t (86-21) 61402666 f (86-21) 64958763 1 (86-21) 61402666

f (86-21) 64958763

www.cn.sgs.com e sas.china@sas.com



No. SH10009758/TX

Date: Jan 27, 2010

Page 2 of 5

Test Result

I. Sample details

Materials / Color	Fabric / Blue	\$ 6° 2		-6
Size of sample	Length: 200± 2mm	Width: 160 ±2mm	32pcs	

Cleaning procedure	BS EN ISO 10528	50 cycles
Per-condition	T: 20± 2 °C H: 65±5 %	24 h

II. Test Conducted

This test is conducted accordance with Type C of BS 5867-2:2008 Specification for Fabrics for curtains, drapes and window blinds - Part2: Flammability requirements and test method is based on BS EN ISO 15025: 2002.

III. Test Results

A) Before any cleaning procedure

The test methods is as per BS EN ISO 15025:2002, Procedure "A" (surface ignition, Flame application time 5s)		Lengthwise		Widthwise	
		1 (Face)	2 (Back)	1 (Face)	2 (Back)
Flame reached an edge	(YES or NO)	NO	NO	NO	NO
Hole reached an edge	(YES or NO)	NO	NO	NO	NO
Flaming debris	(YES or NO)	NO	NO	NO	NO
Duration of flaming	(s)	0	0 9	0	0 _
Duration of Afterglow	(s)	0	0	0	0
Max. vertical extent of hole	(mm)	58	56	54	59
Max. horizontal extent of hole	(mm)	23	25	20	24

The test methods is as per BS EN ISO 15025:2002, Procedure "A" (surface ignition, Flame application time 15s)		Lengthwise		Widthwise	
		1 (Face)	2 (Back)	1 (Face)	2 (Back)
Flame reached an edge	(YES or NO)	NO	NO	NO	NO
Hole reached an edge	(YES or NO)	NO	NO	NO	NO
Flaming debris	(YES or NO)	NO	NO	NO	NO
Duration of flaming	(s)	0	0	0	0
Duration of Afterglow	(s)	0	0	0	0
Max. vertical extent of hole	(mm)	73	69	67	65
Max. horizontal extent of hole	(mm)	29	28	34	26

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://www.sgs.com/terms_and_conditions.htm and interest and conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability to graphing the form and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its jurisdiction of the subject of the company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from the secretary of the subject of the company. The Company is sole responsibility is to its Client and this document does not exonerate parties to a transaction from the secretary of the company. The company is sold the subject of the company is sold the subject of the company is sold to the full of the company of the company. The company is sold the subject of the subjec

SHTX 0 0 8 1 4 3 9

SGS

Test Report

No. SH10009758/TX

Date: Jan 27, 2010

Page 3 of 5

The test methods is as per BS EN ISO 15025:2002, Procedure "A" (surface ignition, Flame application time 20s)		Lengt	hwise	Widthwise	
		1 (Face)	2 (Back)	1 (Face)	2 (Back)
Flame reached an edge	(YES or NO)	NO	NO	NO	NO
Hole reached an edge	(YES or NO)	NO	NO	NO	NO
Flaming debris	(YES or NO)	NO	NO	NO	NO
Duration of flaming	(s)	0	0	0	0
Duration of Afterglow	(s)	0	0	0	0
Max. vertical extent of hole	(mm)	83	76	75	73
Max. horizontal extent of hole	(mm)	30	26	29	25

The test methods is as per BS EN ISO 15025:2002, Procedure "A" (surface ignition, Flame application time 30s)		Lengt	thwise	Widt	hwise
		1 (Face)	2 (Back)	1 (Face)	2 (Back)
Flame reached an edge	(YES or NO)	NO	NO \	NO	NO
Hole reached an edge	(YES or NO)	NO	NO	NO	NO
Flaming debris	(YES or NO)	NO	NO	NO	NO
Duration of flaming	(s)	0	0	0	0
Duration of Afterglow	(s)	0	0	0	0
Max. vertical extent of hole	(mm)	85	76	88	81
Max. horizontal extent of hole	(mm)	32	30	28	31

B) After any cleaning procedure

The test methods is as per BS EN ISO 15025:2002, Procedure "A" (surface ignition, Flame application time 5s)		Lengt	thwise	Widt	hwise
		1 (Face)	2 (Back)	1 (Face)	2 (Back)
Flame reached an edge	(YES or NO)	NO	NO	NO	NO
Hole reached an edge	(YES or NO)	NO	NO	NO	NO
Flaming debris	(YES or NO)	NO	NO	NO	NO
Duration of flaming	(s)	0	0	0	0
Duration of Afterglow	(s)	0	0	0	0
Max. vertical extent of hole	(mm)	57	59	54	58
Max. horizontal extent of hole	(mm)	23	26	21	28

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://www.sgs.com/terms and conditions.

https://www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability fraganities attorn and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its prevention only about thin the limits of Client's instructions, if any. The Company sole responsibility is to its Client and this document does not exonerate parties to a transaction from the severising all their other and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. In unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Junganity of the content of the law.

Junganity of the content of the content of the sample (s) tested and such sample (s) are retained for 30 days only.

SHTX 0 081440

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233

t (86-21) 61402666 f (86-21) 64958763

www.cn.sgs.com e sgs.china@sgs.com



No. SH10009758/TX

Date: Jan 27, 2010

Page 4 of 5

The test methods is as per BS EN ISO 15025:2002, Procedure "A" (surface ignition, Flame application time 15s)		Lengt	Lengthwise		hwise
		1 (Face)	2 (Back)	1 (Face)	2 (Back)
Flame reached an edge	(YES or NO)	NO	NO	NO	NO
Hole reached an edge	(YES or NO)	NO	NO	NO	NO
Flaming debris	(YES or NO)	NO	NO	NO	NO
Duration of flaming	(s)	0	0	0	0
Duration of Afterglow	(s)	0	0	0 8	0
Max. vertical extent of hole	(mm)	66	63	59	65
Max. horizontal extent of hole	(mm)	30	25	24	27

The test methods is as per BS EN ISO 15025:2002, Procedure "A" (surface ignition, Flame application time 20s)		Lengt	hwise	Widt	hwise
		1 (Face)	2 (Back)	1 (Face)	2 (Back)
Flame reached an edge	(YES or NO)	NO	NO	NO	NO
Hole reached an edge	(YES or NO)	NO	NO	NO	NO
Flaming debris	(YES or NO)	NO	NO	NO	NO
Duration of flaming	(s)	0	0	0	0
Duration of Afterglow	(s) \	0	0	0	0
Max. vertical extent of hole	(mm)	75	73	69	70
Max. horizontal extent of hole	(mm)	36	34	39	30

The test methods is as per BS	EN ISO 15025:2002,	Lengthwise		Widthwise	
Procedure "A" (surface ignition	, Flame application time 30s)	1 (Face)	2 (Back)	1 (Face)	2 (Back)
Flame reached an edge	(YES or NO)	NO	NO	NO	NO
Hole reached an edge	(YES or NO)	NO	NO	NO	NO
Flaming debris	(YES or NO)	NO	NO	NO	NO
Duration of flaming	(s)	0	0	0	0
Duration of Afterglow	(s)	0	0	0	0
Max. vertical extent of hole	(mm)	83	78	86	80
Max. horizontal extent of hole	(mm)	47	29	40	36

Criteria:

No part of any hole nor any part of the lowest boundary of any flame shall reach the top edge or either vertical edge of the sample specimen and there shall be no separation of any flaming debris from any specimen, or if the mean afterflame or afterglow times exceed 2.5 s, the fabric shall be deemed not to comply with the requirements for type "C" of this British Standard.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://www.sgs.com/terms_and_conditions. https://www.sgs.com/terms_and_conditions. htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability in the subject of the company is findings at the time of its prevention only and within the limits of Client's Instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for preventions of the subject of th

0081441

e sgs.china@sgs.con

www.cn.sgs.com




No. SH10009758/TX

Date: Jan 27, 2010

Page 5 of 5

Photo Appendix:



<u>Conclusion</u>: The submitted sample meets the requirements of Type C of BS 5867-2:2008.

End of Report



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/terms and conditions http://www.sgs.com/terms and conditions for Electronic Documents at www.sgs.com/terms e-document. <a href="http://www.sgs.com/terms e-document. <

t (86-21) 61402666